

Product datasheet

Specifications



ammeter AMP PowerLogic - 96 x 96
- ferromagnetic - for standard feeder

16074

⚠ Discontinued on: 9 Dec 2024

⚠ Discontinued

Main

Range	PowerLogic
Device short name	AMP
Product or component type	Ammeter
Range compatibility	Prisma Prisma P door Prisma Prisma G door
Technology type	Ferromagnetic
Scale type	80 mm over 90°
Mounting support	Front face

Complementary

Type of measurement	Current
Accuracy class	Class 1.5
Power consumption in VA	1.1 VA
Power consumption in VA	1.1 VA
Overload withstand	1.2 In, permanently 10 In, 5 s
Device mounting	Flush
Operating position	30°/vertical
Width	96 mm
Height	96 mm
Depth	75 mm
Temperature drift	+/- 0.003 %/°C

Environment

Standards	IEC 61010-1 IEC 61000-4 IEC 60051-1
IP degree of protection	IP52
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	11.5 cm
Package 1 Length	11.6 cm
Package 1 Weight	256.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.559 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	76ef2415-e8df-41ac-934d-14936531e31b
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins