

















Proximity Switches

Accessories

Connectors

Selection and Ordering data

Fig.	Type ¹⁾	Cable ²⁾	Length m	Color	Order No.
8 mm cable plugs for snap-on mounting, degree of protection IP66					
Fig. 1 	3-pole, 3 × 0.34 mm ²				
	1	A	PUR	5	Black
Fig. 2 	4-pole, 4 × 0.34 mm ²				
	1	B	PUR	5	Black
Fig. 3 	3-pole, 3 × 0.34 mm ²				
	2	A	PUR	5	Black
Fig. 4 	4-pole, 4 × 0.34 mm ²				
	2	B	PUR	5	Black
Fig. 5 	3-pole, 3 × 0.34 mm ² ; with 2 LEDs for pnp proximity switches				
	3	C	PUR	5	Black/clear
Fig. 6 	4-pole, 4 × 0.34 mm ² ; with 2 LEDs for pnp proximity switches				
	3	C	PUR	10	Black/clear
8 mm angular cable plugs for snap-on mounting, degree of protection IP65					
Fig. 7 	3-pole, 3 × 0.34 mm ²				
	4	A	PUR	5	Black
Fig. 8 	4-pole, 4 × 0.34 mm ²				
	4	A	PUR	10	Black
Fig. 9 	5-pole, 5 × 0.34 mm ²				
	5	A	Coupling plug with soldering pins, max. 0.25 mm ²		Black
Fig. 10 	6-pole, 6 × 0.34 mm ²				
	6	A	Coupling plug with screw connection		Black
M8 cable plugs for screw mounting, degree of protection IP67					
Fig. 11 	3-pole, 3 × 0.34 mm ²				
	4	A	PUR	5	Black
Fig. 12 	4-pole, 4 × 0.34 mm ²				
	4	A	PUR	10	Black
Fig. 13 	5-pole, 5 × 0.34 mm ²				
	5	A	Coupling plug with soldering pins, max. 0.25 mm ²		Black
Fig. 14 	6-pole, 6 × 0.34 mm ²				
	6	A	Coupling plug with screw connection		Black
M8 angular cable plugs for screw mounting, degree of protection IP67					
Fig. 15 	3-pole, 3 × 0.34 mm ²				
	7	A	PUR	5	Black
Fig. 16 	4-pole, 4 × 0.34 mm ²				
	7	A	PUR	10	Black
Fig. 17 	5-pole, 5 × 0.34 mm ²				
	8	A	Coupling plug with soldering pins, max. 0.25 mm ²		Black
Fig. 18 	6-pole, 6 × 0.34 mm ²				
	9	A	Coupling plug with screw connection		Black

Cable plugs with special lengths available as options:

- Minimum order quantity: 50 units
- Delivery time on request.
- Extra charge per m.

¹⁾ For terminal assignment, see page 2/253.

²⁾ PUR cables suitable for trailing.

B: Subject to export regulations: AL = N and ECCN = EAR99