








Fig.	Type ¹⁾	Cable ²⁾	Length m	Color	Approvals	Order No.	
Fig. 18	M8 coupling plugs, degree of protection IP67 For extension cable (metal union nut) with screw-type connection						
	18	3-pole	–	Black		3RX8 000-0BD37	
	18	4-pole	–	Black		3RX8 000-0BD47	
Fig. 19	M12 coupling plugs, degree of protection IP67 for extension cable (metal union nut) with terminal compartment, screw-type terminal max. 0.75 mm ² cable gland max. 6 mm						
	19	L	4-pole	–	Black	3RX8 000-0CD45	
	19	M	5-pole	–	Black	3RX8 000-0CD55	
Fig. 20	20	L	4-pole	Quick connection method	UL	3RX8 000-0CD47	
	M12 angled coupling plug, degree of protection IP67 for extension cable (metal union nut) with terminal compartment, screw-type terminal max. 0.75 mm ² cable gland max. 6 mm						
Fig. 21	21	L	4-pole	–	Black	3RX8 000-0CE45	
	21	M	5-pole	–	Black	3RX8 000-0CE55	
For AS-Interface, degree of protection IP67							
M12 cable plugs 4 × 0.34 mm ² (union nut of metal)							
	22	L	PUR	5	Black	UL, CSA	3RX8 000-0CD42-1AF0
	22	L	PUR	10	Black	UL, CSA	3RX8 000-0CD42-1AL0
M12 angular cable plug 4 × 0.34 mm ² (union nut of metal)							
	23	L	PUR	5	Black		3RX8 000-0CE42-1AF0
	23	L	PUR	10	Black		3RX8 000-0CE42-1AL0
Fig. 22							
Fig. 23							
Fig. 24	Flush-type M12 connector Adapter with single cores, 4-pole with single cores						
	24	• Twistable	0.5			3RX8 000-0CA40-1JA5	
	24	• Not twistable	0.2			3RX8 000-0CA40-1JA2	

Cable plugs with special lengths available as options:

- Minimum order quantity: 50 units
- Delivery time on request.
- Extra charge per m.

1) For terminal assignment, see page 2/253.

2) PUR cables suitable for trailing.