



circuit breaker VL160X N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=40A, rated current Ir=32...40A, overload prot. II=600A, short-circuit prot. without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes with Safety Label for USA

Weight	2 kg
Net Weight	2 kg

Approvals / Certificates

Environment	General Product Approval			
Environmental Con- firmations	Environmental Con- firmations			Confirmation 

Test Certificates	other			
Special Test Certi- cate	Miscellaneous	Confirmation		Miscellaneous

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1704-1DD33-0AA0-Z U01>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL1704-1DD33-0AA0-Z U01>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1704-1DD33-0AA0-Z U01
CAx-Online-Generator
<https://www.siemens.com/cax>
Characteristic curves
https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>



last modified: 11/24/2025 

