



circuit breaker VL160X N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=100A, rated current Ir=80...100A, overload prot. II=1000A, short-circuit prot. without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes with Safety Label for USA

Weight	2 kg
Net Weight	2 kg

Approvals / Certificates

Environment	General Product Approval
-------------	--------------------------



[Confirmation](#)



General Product Approval	EMV	Radio Equipment Type Approval Certificate
--------------------------	-----	---



[Miscellaneous](#)

[Industry Canada \(IC\)](#)

Radio Equipment Type Approval Certificate	Test Certificates	Maritime application
---	-------------------	----------------------

[Miscellaneous](#)

[FCC](#)

[Special Test Certificate](#)

[Miscellaneous](#)



Maritime application	other
----------------------	-------



[Confirmation](#)

[Manufacturer Declaration](#)



Dangerous goods

[Transport Information](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (catalogues, leaflets,...)

<https://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1710-1DD33-0AA0-Z U01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL1710-1DD33-0AA0-Z U01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1710-1DD33-0AA0-Z U01

CAX-Online-Generator
<https://www.siemens.com/cax>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>



last modified:

4/9/2025 

