

SIMATIC S7, TD 200 TEXTDISPLAY FOR S7-200, 2 LINES, WITH CABLE (2.5M) AND MOUNTING ACCESSORIES, CONFIGURATION WITH STEP7-MICRO/WIN W/O ATEX CERTIFICATE



Figure similar

Display	
Design of display	LCD backlit
Line display	
- Number of lines - Number of characters per line - Character size	2 20; Characters/line: ASCII, cyrillic; 10 characters/line: Chinese 5 mm
Supply voltage	
Rated value (DC)	24 V; Power supply via the S7-200 communications interface or optional external power supply unit; the CPU sensor power supply (24 V DC) is not subjected to load
Input current	
Current consumption, max.	120 mA
Interfaces	
Point-to-point	
Transmission rate, max.	187.5 kbit/s
1. Interface	
Physics	RS 485

Functionality	
• PPI	Yes
PPI	
• Number of nodes, max.	126; S7-200, OP, TP, TBP, PG / PC
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP65	Yes; at front
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Dimensions	
Width	148 mm
Height	76 mm
Depth	27 mm
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Overall depth	27 mm
Cabinet/switchboard thickness	0.3 mm; 0.3 to 4 mm
Weights	
Weight, approx.	250 g
last modified:	08.08.2015