



Figura similar

repuesto SIMATIC S7-300, módulo de interfaz IM 361 en bastidor de ampliación para conexión a bastidor central (IM360), tensión de alimentación 24 V DC, con bus K

Tensión de alimentación			
Valor nominal (DC)		Sí	
● 24 V DC			
Intensidad de entrada			
de la tensión de alimentación L+, máx.		500 mA	
Pérdidas			
Pérdidas, típ.		5 W	
Configuración del hardware			
Nº de módulos de interfaz por CPU, máx.		3	
Dimensiones			
Ancho		80 mm	
Altura		125 mm	
Profundidad		120 mm	
Pesos			
Peso, aprox.		505 g	
Clasificaciones			
		Versión	Clasificación
	eClass	16	27-24-22-08
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Homologaciones / Certificados			
General Product Approval			



[Manufacturer Declaration](#)



General Product Approval	EMV	For use in hazardous locations			
--------------------------	-----	--------------------------------	--	--	--

[Manufacturer Declaration](#)



[EM](#)



For use in hazardous locations			Maritime application		
--------------------------------	--	--	----------------------	--	--



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application					
----------------------	--	--	--	--	--



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Última modificación:

7/4/2025