



Figura similar

repuesto SIMATIC S7-300, módulo de interfaz IM 365 para conectar un rack de ampliación, sin bus K, 2 módulos + cable de conexión de 1 m

Intensidad de entrada	
de bus de fondo 5 V DC, máx.	100 mA
Pérdidas	
Pérdidas, típ.	0,5 W
Configuración del hardware	
Nº de módulos de interfaz por CPU, máx.	1; 1 par
Dimensiones	
Ancho	40 mm
Altura	125 mm
Profundidad	120 mm
Pesos	
Peso, aprox.	580 g

Clasificaciones			
		Versión	Clasificación
	eClass	16	27-24-22-08
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Homologaciones / Certificados	
General Product Approval	

[Manufacturer Declaration](#)

    

General Product Approval	EMV	For use in hazardous locations			
Manufacturer Declaration	 RCM	 ATEX	FM	 UL	 IECEX
For use in hazardous locations			Maritime application		
 ATEX	Miscellaneous	CCC-Ex	 ABS	 BUREAU VERITAS	 DNV
Maritime application					
 LRS	NK / Nippon Kaiji Kyokai	 PRS	 RINA	CCS (China Classification Society)	

Última modificación: 7/4/2025 