



Figure similar

Article No. : 6SE6420-2UC21-5BA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
------------	--

Input

Number of phases	1 AC
Line voltage	200 ... 240 V ±10 %
Line frequency	47 ... 63 Hz
Rated current (HO)	14.40 A / 8.30 A

Output

Number of phases	3 AC
Rated voltage	240 V
Rated power (HO)	1.50 kW / 2.00 hp
Rated current (HO)	7.40 A
Pulse frequency	16,000 Hz
Output frequency for V/f control	0...650 Hz
As a result of legal stipulations, a limit to 550 Hz is in production	

Overload capability

High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time

General tech. specifications	
------------------------------	--

Power factor λ 0.95

Efficiency η 0.96

Ambient conditions	
--------------------	--

Cooling Fan

Ambient temperature

Operation (HO) -10...50 °C

Transport -40...70 °C

Storage -40...70 °C



Figure similar

Article No. : 6SE6420-2UC21-5BA1

Mechanical data	
Degree of protection	IP20 / UL open type
Frame size	FSB
Net weight	3.30 kg
Width	149.0 mm
Height	202.0 mm
Depth	172.0 mm

Inputs / outputs	
Standard digital inputs	
Number	3
Relay output	
Number	1
Analog inputs	
Number	1
Analog outputs	
Number	1

Connections	
Motor end	
Conductor cross-section	6.00 mm²