

Specifications



Eaton DILM25-10(24V60HZ)

Eaton XT IEC large contactor, 25A, 24 Vac, 60 Hz, 1NO, 25A, Frame C, 45 mm, 60 Hz, 2, 5/7.5, 10, 15, 20 (1/3PH @120, 240/208, 240, 480, 600 V), Three-pole, Non-reversing, , Screw terminals, FVNR, 11 kW

Photo is representative



General specifications

PRODUCT NAME	Eaton XT IEC large contactor
CATALOG NUMBER	DILM25-10(24V60HZ)
EAN	4015082771232
PRODUCT LENGTH/DEPTH	3.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	4 in
PRODUCT WEIGHT	1 lb
WARRANTY	1 year
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)
PRODUCT TYPE	Large contactors

Product specifications

AMPERAGE RATING	25A
HP RATING - MAX	2, 5/7.5, 10, 15, 20 (1/3PH @120,240/208,240,480,600 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
FREQUENCY RATING	60 Hz
FRAME SIZE	45 mm
TERMINALS	Screw terminals
COIL	24 Vac 60 Hz
COIL VOLTAGE	24 Vac, 60 Hz
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	25 A
SERIES	XT IEC
OPERATION	Non-reversing
POWER CONSUMPTION	11 kW

Resources

MULTIMEDIA

[S1. E4. Ask the Experts - NEMA, IEC and DP contactors](#)

[Contactors Explained](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - DILM25-10\(24V60HZ\)](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

